

FLOTATION 647 - Teknik Özellikler



Description

FLOTATION 647, yumuşak toprak ve çim sahalarda en iyi çekiş özelliğine sahip bir uygulama lastiğidir. Mükemmel kendi kendini temizleme özelliklerine ek olarak, özel olarak tasarlanmış sırt deseni, en uygun zemin basıncı ve yumuşak toprakta mükemmel performans sağlayan geniş bir temas alanı sağlar.

UM

International Standard

Construction

❖ BIAS

Machinery

Zirai: Uygulamalı makine

Version	STANDARD
Type	TL
Tyre Size	520/50 - 17
LI/SS DRIVE WHEEL	147 B
LI/SS FREE ROLLING	159 B

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	965
Static Loaded Radius (mm)	426
Rolling Circumference (mm)	2907
Rim Rec	AG 16.00
ECE	E11-106R-005770

Load capacity (Kg)

km/h / bar	4.00
50 FR	4375
50 DW	3075

Printed on 4/26/2024 6:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..