

FLOTATION 648 T - Teknik Özellikler

Description

FLOTATION 648 T, özellikle saman hasadının yanı sıra arazi ve kara yolu taşımacılığı için de uygundur. Özel sırt tasarımı, çok ağır yüklerin düşük basınçta taşınmasına olanak tanır ve üstün kendi kendini temizleme özellikleri sağlar. Lastik ayrıca mükemmel çekiş ve dayanıklılık anlamına gelir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Saman biçerdöveri



| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 550/45 - 22.5 |
| LI/SS DRIVE WHEEL | 154 A8/150 B |
| LI/SS FREE ROLLING | 166 A8/162 B |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Ply Rating | 20 |
| Section Width (mm) | 550 |
| Overall Diameter (mm) | 1070 |
| Static Loaded Radius (mm) | 475 |
| Rolling Circumference (mm) | 3203 |
| Rim Rec | AG 16.00 |
| ECE | E4-106R-002046 |

Load capacity (Kg)

| km/h / bar | 3.00 | 3.50 | 4.00 |
|------------|------|------|------|
| 10 FR | 6270 | 6860 | 7420 |
| 20 FR | 5645 | 6175 | 6680 |
| 30 FR | 5020 | 5490 | 5935 |
| 40 FR | 4480 | 4900 | 5300 |
| 50 FR | 4030 | 4410 | 4750 |
| 10 DW | 4440 | 4860 | 5250 |
| 20 DW | 3995 | 4370 | 4725 |
| 30 DW | 3550 | 3885 | 4200 |
| 40 DW | 3170 | 3470 | 3750 |
| 50 DW | 2855 | 3125 | 3350 |

Printed on 4/26/2024 11:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..