

FLOTATION 648 - Teknik Özellikler



Description

FLOTATION 648, özellikle arazi ve kara yolu taşımacılığının yanı sıra yayma operasyonları için de uygundur. Bazı ebatlar saman hasadı/balyalama makineleri için tasarlanmıştır. Özel sırt tasarımı, düşük basınçta çok ağır yüklerin taşınmasına izin verir, aynı zamanda daha az toprak sıkışması garanti eder ve ekinlerin zarar görmesini önler.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Yayıcı

Version	STANDARD
Type	TL
Tyre Size	385/65 - 22.5 (400/60 - 22.5)
LI/SS DRIVE WHEEL	155 A8/151 B
LI/SS FREE ROLLING	167 A8/163 B

Dimensions US Standard

Usa code	94031443
Ply Rating	22
Section Width (inch)	15.7
Overall Diameter (inch)	42.1
Static Loaded Radius (inch)	18.7
Rolling Circumference (inch)	127.3
Rim Rec	AG 11.75
ECE	E11-106R-004388

Load capacity (lbs)

mph / psi	77	81	86
5 FR	15810	16310	16820
10 FR	14220	14680	15130
20 FR	12640	13050	13460
25 FR	11290	11650	12010
30 FR	10160	10480	10750
5 DW	11230	11610	11960
10 DW	10110	10450	10770
20 DW	8980	9280	9570
25 DW	8020	8290	8540
30 DW	7220	7460	7610

Printed on 4/24/2024 11:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..