

FLOTATION 648 - Teknik Özellikler



Description

FLOTATION 648, özellikle arazi ve kara yolu taşımacılığının yanı sıra yayma operasyonları için de uygundur. Bazı ebatlar saman hasadı/balyalama makineleri için tasarlanmıştır. Özel sırt tasarımı, düşük basınçta çok ağır yüklerin taşınmasına izin verir, aynı zamanda daha az toprak sıkışması garanti eder ve ekinlerin zarar görmesini önler.

UM

International Standard

Construction

❖ BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Yayıcı

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS DRIVE WHEEL	137 A8/133 B
LI/SS FREE ROLLING	149 A8/145 B

Dimensions International Standard

Ply Rating	14
Section Width (mm)	510
Overall Diameter (mm)	945
Static Loaded Radius (mm)	416
Rolling Circumference (mm)	2750
Rim Rec	AG 16.00
ECE	E4-106R-001885

Load capacity (Kg)

km/h / bar	2.20	2.40	2.80
10 FR	3950	4160	4550
20 FR	3555	3740	4095
30 FR	3160	3325	3640
40 FR	2820	2970	3250
50 FR	2540	2675	2900
10 DW	2795	2940	3220
20 DW	2515	2645	2900
30 DW	2235	2350	2575
40 DW	1995	2100	2300
50 DW	1795	1890	2060

Printed on 12/8/2023 1:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..