

FLOTATION 648 - Teknik Özellikler



Description

FLOTATION 648, özellikle arazi ve kara yolu taşımacılığının yanı sıra yayma operasyonları için de uygundur. Bazı ebatlar saman hasadı/balyalama makineleri için tasarlanmıştır. Özel sırt tasarımı, düşük basınçta çok ağır yüklerin taşınmasına izin verir, aynı zamanda daha az toprak sıkışması garanti eder ve ekinlerin zarar görmesini önler.

UM

US Standard

Construction

❖ BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Yayıcı

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 550/60 - 22.5 |
| LI/SS DRIVE WHEEL | 148 A8/144 B |
| LI/SS FREE ROLLING | 160 A8/156 B |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94006373 |
| Ply Rating | 12 |
| Section Width (inch) | 21.7 |
| Overall Diameter (inch) | 48.8 |
| Static Loaded Radius (inch) | 21.3 |
| Rolling Circumference (inch) | 146.7 |
| Rim Rec | AG 16.00 |
| ECE | E4-106R-002310 |

Load capacity (lbs)

| mph / psi | 22 | 26 | 30 |
|-----------|-------|-------|-------|
| 5 FR | 11410 | 12690 | 13890 |
| 10 FR | 10260 | 11420 | 12500 |
| 20 FR | 9130 | 10150 | 11110 |
| 25 FR | 8150 | 9060 | 9920 |
| 30 FR | 7330 | 8160 | 8820 |
| 5 DW | 7980 | 8880 | 9720 |
| 10 DW | 7180 | 8000 | 8750 |
| 20 DW | 6380 | 7110 | 7780 |
| 25 DW | 5700 | 6350 | 6940 |
| 30 DW | 5130 | 5710 | 6170 |

Printed on 11/29/2023 5:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..