

FLOTATION 648 - Teknik Özellikler



Description

FLOTATION 648, özellikle arazi ve kara yolu taşımacılığının yanı sıra yayma operasyonları için de uygundur. Bazı ebatlar saman hasadı/balyalama makineleri için tasarlanmıştır. Özel sırt tasarımı, düşük basınçta çok ağır yüklerin taşınmasına izin verir, aynı zamanda daha az toprak sıkışması garanti eder ve ekinlerin zarar görmesini önler.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Yayıcı

Version	STANDARD
Type	TL
Tyre Size	600/50 - 22.5
LI/SS DRIVE WHEEL	155 A8/151 B
LI/SS FREE ROLLING	167 A8/163 B

Dimensions US Standard

Usa code	94030781
Ply Rating	18
Section Width (inch)	24.1
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.1
Rolling Circumference (inch)	137.8
Rim Rec	AG 20.00
ECE	E4-106R-002275

Load capacity (lbs)

mph / psi	39	41	42
5 FR	16130	16480	16820
10 FR	14520	14840	15130
20 FR	12900	13180	13460
25 FR	11520	11770	12010
30 FR	10370	10590	10750
5 DW	11460	11720	11960
10 DW	10320	10540	10770
20 DW	9170	9370	9570
25 DW	8190	8370	8540
30 DW	7370	7530	7610

Printed on 12/7/2023 11:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..