

## FLOTATION 648 - Teknik Özellikler



### Description

FLOTATION 648, özellikle arazi ve kara yolu taşımacılığının yanı sıra yayma operasyonları için de uygundur. Bazı ebatlar saman hasadı/balyalama makineleri için tasarlanmıştır. Özel sırt tasarımı, düşük basınçta çok ağır yüklerin taşınmasına izin verir, aynı zamanda daha az toprak sıkışması garanti eder ve ekinlerin zarar görmesini önler.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Yayıcı

Version	STANDARD
Type	TL
Tyre Size	650/65 - 30.5
LI/SS DRIVE WHEEL	167 A8/163 B
LI/SS FREE ROLLING	179 A8/175 B

## Dimensions US Standard

Usa code	94006465
Ply Rating	16
Section Width (inch)	26.4
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 20.00
ECE	E4-106R-001550

## Load capacity (lbs)

mph / psi	26	29	32
5 FR	21260	22620	23920
10 FR	19140	20360	21530
20 FR	17010	18100	19140
25 FR	15190	16160	17080
30 FR	13670	14540	15210
5 DW	14960	15910	16820
10 DW	13460	14320	15130
20 DW	11960	12730	13460
25 DW	10680	11360	12010
30 DW	9610	10230	10750

Printed on 4/24/2024 6:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..