

FLOTATION 648 - Teknik Özellikler



Description

FLOTATION 648, özellikle arazi ve kara yolu taşımacılığının yanı sıra yayma operasyonları için de uygundur. Bazı ebatlar saman hasadı/balyalama makineleri için tasarlanmıştır. Özel sırt tasarımı, düşük basınçta çok ağır yüklerin taşınmasına izin verir, aynı zamanda daha az toprak sıkışması garanti eder ve ekinlerin zarar görmesini önler.

UM

US Standard

Construction

❖ BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Yayıcı

Version	HIGH SPEED
Type	TL
Tyre Size	700/50 - 22.5
LI/SS DRIVE WHEEL	158 B/154 E
LI/SS FREE ROLLING	170 B/166 E

Dimensions US Standard

Usa code	94025596
Ply Rating	16
Section Width (inch)	27.6
Overall Diameter (inch)	50
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	148.6
Rim Rec	24.00
ECE	E11-106R-004555

Load capacity (lbs)

mph / psi	29	32	35
5 FR	18580	19640	20680
10 FR	16720	17680	18610
20 FR	14860	15720	16540
25 FR	13270	14030	14770
30 FR	11950	12630	13230
45 FR	10480	11090	11680
5 DW	13180	13930	14660
10 DW	11860	12540	13190
20 DW	10540	11140	11730
25 DW	9410	9950	10470
30 DW	8480	8960	9370
45 DW	7440	7860	8270

Printed on 4/24/2024 4:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..