

FLOTATION 648 - Teknik Özellikler



Description

FLOTATION 648, özellikle arazi ve kara yolu taşımacılığının yanı sıra yayma operasyonları için de uygundur. Bazı ebatlar saman hasadı/balyalama makineleri için tasarlanmıştır. Özel sırt tasarımı, düşük basınçta çok ağır yüklerin taşınmasına izin verir, aynı zamanda daha az toprak sıkışması garanti eder ve ekinlerin zarar görmesini önler.

UM

International Standard

Construction

❖ BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Yayıcı

Version	STANDARD
Type	TL
Tyre Size	700/50 - 22.5
LI/SS DRIVE WHEEL	162 A8/158 B
LI/SS FREE ROLLING	174 A8/170 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	700
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	550
Rolling Circumference (mm)	3775
Rim Rec	24.00
ECE	E4-106R-001566

Load capacity (Kg)

km/h / bar	2.00	2.20	2.40
10 FR	8430	8910	9380
20 FR	7585	8020	8440
30 FR	6740	7130	7505
40 FR	6020	6365	6700
50 FR	5420	5730	6000
10 DW	5980	6320	6650
20 DW	5380	5690	5985
30 DW	4780	5055	5320
40 DW	4270	4515	4750
50 DW	3845	4065	4250

Printed on 12/8/2023 1:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..