

## FLOTATION 648 - Teknik Özellikler



### Description

FLOTATION 648, özellikle arazi ve kara yolu taşımacılığının yanı sıra yayma operasyonları için de uygundur. Bazı ebatlar saman hasadı/balyalama makineleri için tasarlanmıştır. Özel sırt tasarımı, düşük basınçta çok ağır yüklerin taşınmasına izin verir, aynı zamanda daha az toprak sıkışması garanti eder ve ekinlerin zarar görmesini önler.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Yayıcı

Version	STANDARD
Type	TL
Tyre Size	800/45 - 26.5
LI/SS DRIVE WHEEL	170 A8/167 B
LI/SS FREE ROLLING	183 A8/180 B

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Section Width (mm)</b>	800
<b>Overall Diameter (mm)</b>	1393
<b>Static Loaded Radius (mm)</b>	631
<b>Rolling Circumference (mm)</b>	4185
<b>Rim Rec</b>	AG 28.00
<b>ECE</b>	E11-106R-004618

## Load capacity (Kg)

km/h / bar	2.60	2.70	2.80
10 FR	11730	11990	12250
20 FR	10560	10790	11025
30 FR	9385	9595	9800
40 FR	8380	8565	8750
50 FR	7540	7710	8000
10 DW	8045	8225	8400
20 DW	7240	7405	7560
30 DW	6435	6580	6720
40 DW	5745	5875	6000
50 DW	5170	5290	5450

Printed on 4/24/2024 10:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..