

FLOTATION RIB 774 - Teknik Özellikler



Description

FLOTATION RIB 774, tüm serbest dönen uygulamalar, saman hasadı uygulamaları için uygundur ve römorklar için idealdir. Yüksek yük kapasitesi ve daha uzun lastik ömrünün yanı sıra operasyonların zamanlamasını optimize eden en iyi kullanım konforunu sağlamak üzere tasarlanmıştır.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Biçerdöver • Saman biçerdöveri • Römork

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS FREE ROLLING	160 A8/156 B

Dimensions US Standard

Usa code	94006601
Ply Rating	12
Section Width (inch)	21.7
Overall Diameter (inch)	48.8
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	146.7
Rim Rec	AG 16.00
ECE	E11-106R-005941

Load capacity (lbs)

mph / psi	22	26	30
5 FR	11410	12690	13890
10 FR	10260	11420	12500
20 FR	9130	10150	11110
25 FR	8150	9060	9920
30 FR	7330	8160	8820

Printed on 4/23/2024 10:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..