

## FLOTATION RIB 774 - Teknik Özellikler



### Description

FLOTATION RIB 774, tüm serbest dönen uygulamalar, saman hasadı uygulamaları için uygundur ve römorklar için idealdir. Yüksek yük kapasitesi ve daha uzun lastik ömrünün yanı sıra operasyonların zamanlamasını optimize eden en iyi kullanım konforunu sağlamak üzere tasarlanmıştır.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Biçerdöver • Saman biçerdöveri • Römork

Version	STANDARD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS FREE ROLLING	167 A8/163 B

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	550
Overall Diameter (mm)	1240
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3725
Rim Rec	AG 16.00
ECE	E11-106R-005942

## Load capacity (Kg)

km/h / bar	2.40	2.60	2.80
10 FR	6970	7310	7630
20 FR	6275	6575	6865
30 FR	5580	5845	6105
40 FR	4980	5220	5450
50 FR	4480	4700	4875

Printed on 4/23/2024 9:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..