

FLOTATION TR 678 - Teknik Özellikler



Description

FLOTATION TR 678, hem yolda hem de yol dışında römorklar ve tarım uygulamaları için özel olarak tasarlanmıştır. Bu lastik, aynı zamanda daha az toprak sıkışması sağlayarak düşük basınçta çok ağır yüklerin taşınmasına olanak tanır. Mükemmel çekiş ve üstün kendi kendini temizleme özellikleri sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TT
Tyre Size	320/60 - 12
LI/SS DRIVE WHEEL	120 A8
LI/SS FREE ROLLING	132 A8

Dimensions International Standard

Section Width (mm)	328
Overall Diameter (mm)	689
Static Loaded Radius (mm)	327
Rolling Circumference (mm)	2111
Rim Rec	10.50 I
ECE	E11-106R-006617

Load capacity (Kg)

km/h / bar	4.00
40 FR	2000
40 DW	1400

Printed on 2/26/2024 9:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..