

## FLOTATION TR 678 - Teknik Özellikler



### Description

FLOTATION TR 678, hem yolda hem de yol dışında römorklar ve tarım uygulamaları için özel olarak tasarlanmıştır. Bu lastik, aynı zamanda daha az toprak sıkışması sağlayarak düşük basınçta çok ağır yüklerin taşınmasına olanak tanır. Mükemmel çekiş ve üstün kendi kendini temizleme özellikleri sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Uygulamalı makine • Römork

|                    |               |
|--------------------|---------------|
| Version            | INDUSTRIAL    |
| Type               | TL            |
| Tyre Size          | 600/40 - 22.5 |
| LI/SS DRIVE WHEEL  | 157 A8        |
| LI/SS FREE ROLLING | 169 A8        |

## Dimensions International Standard

|                                   |          |
|-----------------------------------|----------|
| <b>Ply Rating</b>                 | 20       |
| <b>Section Width (mm)</b>         | 615      |
| <b>Overall Diameter (mm)</b>      | 1085     |
| <b>Static Loaded Radius (mm)</b>  | 483      |
| <b>Rolling Circumference (mm)</b> | 3264     |
| <b>Rim Rec</b>                    | AG 20.00 |

## Load capacity (Kg)

|  |              |             |
|--|--------------|-------------|
|  | km/h / bar   | <b>4.10</b> |
|  | <b>40 FR</b> | 5800        |
|  | <b>40 DW</b> | 4125        |

Printed on 2/26/2024 9:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..