

FLOTATION TR 678 - Teknik Özellikler



Description

FLOTATION TR 678, hem yolda hem de yol dışında römorklar ve tarım uygulamaları için özel olarak tasarlanmıştır. Bu lastik, aynı zamanda daha az toprak sıkışması sağlayarak düşük basınçta çok ağır yüklerin taşınmasına olanak tanır. Mükemmel çekiş ve üstün kendi kendini temizleme özellikleri sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	650/45 - 22.5
LI/SS	160 D

Dimensions International Standard

Section Width (mm)	650
Overall Diameter (mm)	1150
Static Loaded Radius (mm)	502
Rolling Circumference (mm)	3302
Rim Rec	AG 20.00
ECE	E11-106R-004399

Load capacity (Kg)

km/h / bar	4.00
65	4875

Printed on 4/20/2024 4:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..