

FLOTATION V LINE - Veri Sayfasını İndir



Description

FLOTATION V LINE taşıma uygulamalarında kullanılan römorklar için özel olarak tasarlanmıştır. Yüksek flotasyon kabiliyetine sahiptir ve düşük seviyede toprak sıkışması sağlayarak araziyi korur. FLOTATION V LINE ağır yükleri düşük basınçta taşımanıza imkan verir ve işletmenizin verimliliğini maksimuma çıkarır.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Römork

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/60 - 22.5	STANDARD	94006205	145 A8/142 B	157 A8/154 B	12	AG 16.00	15.00 ; 17.00	19.7	46.1	20.1	137.4	TL	E4-106R-001561
500/60 - 22.5	STANDARD	94006212	151 A8/ 148 B	163 A8/159 B	16	AG 16.00	15.00 ; 17.00	19.7	46.1	20.1	137.4	TL	E4-106R-001562
550/60 - 22.5	STANDARD	94006229	148 A8/144 B	160 A8/ 156 B	12	AG 16.00		21.7	48.8	21.3	146.7	TL	
550/60 - 22.5	STANDARD	94006236	154 A8/150 B	167 A8/163 B	16	AG 16.00		21.7	48.8	21.3	146.7	TL	E4-106R-001563

Printed on 4/27/2024 10:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..