

FORESTECH - Teknik Özellikler



Description

FORESTECH taşıyıcılarla yapılan ormancılık uygulamaları için uygun bir çelik kuşaklı, radyal BKT lastiğidir. Ağır yük gerektiren işlerde bile kusursuz çekiş sağlar. Güçlü damak ve omuz bölgesi, uzun lastik ömrünün yanı sıra delinmelere karşı yüksek dayanıklılık sağlar. Sonuç olarak, ormanda en zor çalışma koşullarıyla bile sorunsuzca başa çıkabilirsiniz.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Yükleyici taşıyıcı

Version	STEEL BELTED
Type	TL
Tyre Size	750/55 - 26.5
LI/SS	177 A8/184 A2

Dimensions US Standard

Usa code	94031719
Ply Rating	20
Section Width (inch)	29.7
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	175.9
Rim Rec	AG 24.00
ECE	E11-106R-003347
TRA Code	LS2

Load capacity (lbs)

mph / psi	73
25	16090
20	17220
5	19840

Printed on 4/26/2024 7:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..