

FS 216 - Teknik Özellikler



Description

FS 216 tomruk yükleyici ve iticileri için çekiş performansını iyileştirmek üzere en uygun açığı ve daha fazla genişliği kapsayan, sağlam çekme tasarımına sahiptir. Lastik, en zorlu çalışma koşullarında bile kesilme ve parçalanmaya karşı kusursuz dayanıklılık sağlar ve olası zararlara karşı her zaman maksimum koruma sunar.

UM

US Standard

Construction

❖ BIAS

Machinery

Zirai: Tomruk yükleme

Version	STEEL BELTED
Type	TL
Tyre Size	24.5 - 32

Dimensions US Standard

Usa code	94033669
Ply Rating	16
Section Width (inch)	24.5
Overall Diameter (inch)	72.1
Static Loaded Radius (inch)	32.9
Rolling Circumference (inch)	214.8
Rim Rec	DH 21
Rim Alt	DH 21 B
ECE	E11-106R-003421
TRA Code	LS2

Load capacity (lbs)

mph / psi	35	30
5	15400	-
20	-	11000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 1:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..