

GF 304 - Teknik Özellikler



Description

GF 304, golf arabaları kullanılan golf uygulamaları için uygundur. GF 304 en iyi konforu ve çim korumasını sağlar. GF 304 ayrıca delinme direncini arttırmak için "aramid kuşaklı" versiyonu da sunulmaktadır.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Golf aracı

Version	STANDARD
Type	TL
Tyre Size	18 X 8.50 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	216
Overall Diameter (mm)	460
Static Loaded Radius (mm)	202
Rolling Circumference (mm)	1334
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003442

Load capacity (Kg)

km/h / bar	1.50
15	375

Printed on 4/18/2024 3:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..