

GF 305 FARM TRAILER - Teknik Özellikler



Description

GF 305 FARM TRAILER, taşıma operasyonlarındaki uygulamalı makineler için özel olarak tasarlanmıştır. Bu lastik zemine doğal bir şekilde nazik davranır ve sahayı hasara karşı korur.

UM

International Standard

Construction



Machinery

Zirai: Uygulamalı makine

Version	STANDARD
Туре	TL
Tyre Size	205/65 - 10 (20.5 x 8.00 - 10)

Dimensions International Standard

Ply Rating	10
Section Width (mm)	212
Overall Diameter (mm)	520
Static Loaded Radius (mm)	223
Rolling Circumference (mm)	1508
Rim Rec	6.00
ECE	E11-106R-003578

Load capacity (Kg)

km/h / bar	6.20
40	695

Printed on 4/20/2024 3:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..