GIANT TRAX - Teknik Özellikler

Description

GIANT TRAX hurdalıklar ve geri dönüşüm işlemlerinin yanı sıra madencilik uygulamalarında da görebileceğiniz nokta dönüşlü yükleyicilerin engebeli zeminlerdeki çalışma koşulları için tasarlanmıştır. Daha geniş ve sağlam bloklu ekstra derin deseni en iyi çekişi, istikrarı ve delinmelere karşı dayanıklılığı sağlar. Özel diş bileşiği kesilme ve parçalanmalara karşı sıra dışı dayanıklılıkla birlikte, her tür arazide aşınmaya karşı kusursuz direnç sağlar.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Mini yükleyici

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions US Standard

Usa code	94045860
Ply Rating	14
Section Width (inch)	12.4
Overall Diameter (inch)	33.1
Static Loaded Radius (inch)	15.7
Rolling Circumference (inch)	99.3
Rim Rec	9.75
ECE	E11-106R-005562

Load capacity (lbs)

mph / psi	90
5	6780
10	5360
15	4950

Printed on 4/29/2024 9:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..