

## GR 288 - Teknik Özellikler



### Description

GR 288 (G-2/L-2) greyderler ve yükleyiciler için çok yönlü, çapraz kuşaklı bir lastiktir. İnşaat, şantiye hazırlığı, yol yapımı ve diğer yumuşak veya çamurlu ortamlarda kullanım için idealdir. Kendini temizleyen deseni kusursuz çekiş sağlar ve kesilme ve parçalanmalara karşı dayanıklı özel bileşik sayesinde uzun lastik ömrü sunar.

### UM

International Standard

### Construction

BIAS

### Machinery

Endüstriyel: Dozer • Yükleyici  
Yoldışı: Greyder

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

## Dimensions International Standard

Ply Rating	20
Overall Width (mm)	520
Overall Diameter (mm)	1480
Static Loaded Radius (mm)	656
Rolling Circumference (mm)	4396
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
ECE	E11-106R-005180
TRA Code	G2/L2

## Load capacity (Kg)

km/h / bar	2.75	4.50
40	4500	-
10	-	9500

Printed on 4/28/2024 11:54 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..