

GRIP STAR - Teknik Özellikler



Description

GRIP STAR teleskopik taşıyıcılarla yapılan yükleme uygulamaları için bir tarım sınai lastiğidir. Kusursuz çekiş ve kendini temizleme özellikleri sunar. Ayrıca, çamurlu zemindeki çalışmalar için uygun bir dört mevsim lastiğidir. GRIP STAR, kesilme ve parçalanmalara karşı ekstra dayanıklılık sağlayan "özel" modeliyle de mevcuttur.

UM

US Standard

Construction

 BIAS

Machinery

Endüstriyel: Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	15.5/80 - 24
LI/SS DRIVE WHEEL	151 A6
LI/SS FREE ROLLING	163 A6

Dimensions US Standard

Usa code	94019762
Ply Rating	16
Section Width (inch)	15.4
Overall Diameter (inch)	50
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	145
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L

Load capacity (lbs)

mph / psi	58
20 FR LLV	10750
20 DW LLV	7610

Printed on 4/27/2024 10:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..