

## HARVESTER SPECIAL - Teknik Özellikler



### Description

HARVESTER SPECIAL, biçerdöverler için özel olarak tasarlanmıştır. Çift açılı dişleri, tarlalarda mükemmel çekiş ve yolda konforlu bir sürüş sağlar. Özel sırt tasarımı, olağanüstü sabitleme için geniş bir temas alanı sağlar. HARVESTER SPECIAL, daha uzun bir lastik kullanım ömrüne olanak tanıyan güçlü bir gövdeye ve özellikle kesilmeye ve kopmaya karşı dirençli bir hamura sahiptir.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Biçerdöver

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26
LI/SS	159 A6

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	587
Overall Diameter (mm)	1585
Static Loaded Radius (mm)	720
Rolling Circumference (mm)	4806
Rim Rec	DW 20 B ; DW 20 A
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.30
30	4375

Printed on 4/26/2024 11:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..