

HARVESTER SPECIAL - Teknik Özellikler



Description

HARVESTER SPECIAL, biçerdöverler için özel olarak tasarlanmıştır. Çift açılı dişleri, tarlalarda mükemmel çekiş ve yolda konforlu bir sürüş sağlar. Özel sırt tasarımı, olağanüstü sabitleme için geniş bir temas alanı sağlar. HARVESTER SPECIAL, daha uzun bir lastik kullanım ömrüne olanak tanıyan güçlü bir gövdeye ve özellikle kesilmeye ve kopmaya karşı dirençli bir hamura sahiptir.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Biçerdöver

Version	DUAL BEAD
Type	TL
Tyre Size	23.5 - 25
LI/SS	191 A2

Dimensions International Standard

Ply Rating	20
Section Width (mm)	615
Overall Diameter (mm)	1665
Static Loaded Radius (mm)	715
Rolling Circumference (mm)	5058
Rim Rec	19.50/2.5
ECE	E11-106R-006954
TRA Code	R1

Load capacity (Kg)

km/h / bar	3.75
10	10900

Printed on 4/26/2024 9:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..