I - 1 - Teknik Özellikler

Description

I-1 uygulamalı makineler ve römorklar ile arazi ve kara yolu taşımacılığı ve toprak işleme operasyonları için tasarlanmıştır. I-1, asıl işinize odaklanabilmeniz için seyahat sürelerinizi optimize eden yüksek hızlı bir lastiktir. Özel tasarımı zorlu koşullarda ve arazilerde anız olması durumunda uzun kullanım ömrü sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	7.60 - 15 SL
LI/SS	106 D

Dimensions International Standard

Ply Rating	8
Section Width (mm)	193
Overall Diameter (mm)	734
Static Loaded Radius (mm)	328
Rolling Circumference (mm)	2151
Rim Rec	5.50
Rim Alt	6 LB
TRA Code	I1

Load capacity (Kg)

km/h / bar	3.60
65	950

Printed on 4/29/2024 12:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..