

## INDUSTRIAL RIB F3 - Teknik Özellikler



### Description

INDUSTRIAL RIB F3 uygulamalı makineler ve römorklar ile arazi ve kara yolu taşımacılığı ve toprak işleme operasyonları için tasarlanmış, kuşaklı desene sahip bir tarımsal sanayi lastiğidir. Bu lastik, anızlara olağanüstü dayanıklı hamuruyla en kritik çalışma koşullarına uygundur ve uzun lastik kullanım ömrü sağlar.

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	11L - 16 SL
LI/SS	120 A6

## Dimensions US Standard

Usa code	94000173
Ply Rating	12
Section Width (inch)	11
Overall Diameter (inch)	32.7
Rim Rec	W 8 L
Rim Alt	8 LB ; 10 LB ; W 10 L
ECE	E11-106R-004306
TRA Code	F3

## Load capacity (lbs)

mph / psi	64
20	3050
25	2760

Printed on 4/23/2024 5:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..