

LG 306 - Teknik Özellikler



Description

LG 306, çim biçme makineleri için uygun bir çim ve bahçe lastiğidir. LF 306, bazı ebatlarda küçük traktörler için de uygundur. Özel sırt deseni, lastiğin zemine nazik davranmasını sağlar ve aynı zamanda kullanımı kolaylaştırır. LG 306'nın, güçlendirilmiş delinme direncine ihtiyaç duyan kullanıcılar için "aramid kuşaklı" versiyonu da mevcuttur.

UM

US Standard

Construction

❖ BIAS

Machinery

Zirai: Biçme makineleri • Küçük Traktör

| | |
|-----------|----------------|
| Version | ARAMID BELTED |
| Type | TL |
| Tyre Size | 23 X 8.50 - 12 |

Dimensions US Standard

| | |
|------------------------------|-------------------------------|
| Usa code | 94028252 |
| Ply Rating | 6 |
| Section Width (inch) | 8.3 |
| Overall Diameter (inch) | 22.6 |
| Static Loaded Radius (inch) | 10.2 |
| Rolling Circumference (inch) | 67.3 |
| Rim Rec | 7.00 I - 55 ; I - 70 ; I - 90 |
| Rim Alt | 7 JA |
| ECE | E11-106R-004409 |

Load capacity (lbs)

| mph / psi | 34 |
|-----------|------|
| 10 | 1430 |

Printed on 4/20/2024 3:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..