

LG SMOOTH - Teknik Özellikler



Description

LG SMOOTH biçme makineleri için uygun bir çim ve bahçe lastiğidir. Lastik zemin üzerinde hafiflik sunarken, geliştirilmiş tasarım daha fazla dayanıklılık sağlar ve yol tutuşu kolaylaştırır. LG SMOOTH, delinmelere karşı daha güçlü dirence ihtiyaç duyan kullanıcılar için "aramid kuşaklı" modeliyle de sunulmaktadır.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Biçme makineleri • Küçük Traktör

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 10

Dimensions International Standard

Ply Rating	4
Section Width (mm)	245
Overall Diameter (mm)	500
Static Loaded Radius (mm)	223
Rolling Circumference (mm)	1450
Rim Rec	8.00 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003470

Load capacity (Kg)

km/h / bar	1.50
15	530

Printed on 2/22/2024 6:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..