

LIFTMAX LM 63 - Teknik Özellikler



Description

LIFTMAX LM 63, endüstriyel ve lojistik operasyonlar için özel olarak geliştirilmiştir. 3 kanallı sırt tasarımı, iyi ıslak yol tutuşu ile düşük dönme direnci ve daha iyi kavrama ile düzgün sırt aşınması sağlar. Daha düşük titreşim, daha fazla sabitleme ve konfor sunan çok katmanlı çelik kayışlara sahip bir Tamçelik radyal lastiktir.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Saman biçerdöveri

Endüstriyel: Tow Tractor • Römork

Version	STANDARD
Type	TL
Tyre Size	180/70 R 8 IMP (18X7 R 8)
LI/SS	120 A8

Dimensions International Standard

Overall Width (mm)	170
Overall Diameter (mm)	460
Rim Rec	4.33R
ECE	E11-106R-006845

Load capacity (Kg)

km/h / bar	10.00
40	1400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/15/2024 2:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..