



LIFTMAX LM 63 - Veri Sayfasını İndir

Description

LIFTMAX LM 63, endüstriyel ve lojistik operasyonlar için özel olarak geliştirilmiştir. 3 kanallı sırt tasarımı, iyi ıslak yol tutuşu ile düşük dönme direnci ve daha iyi kavrama ile düzgün sırt aşınması sağlar. Daha düşük titreşim, daha fazla sabitleme ve konfor sunan çok katmanlı çelik kayışlara sahip bir Tamçelik radyal lastiktir.



UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Saman biçerdöveri

Endüstriyel: Tow Tractor • Römork

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type	ECE
180/70 R 8 (18X7 R 8)	STANDARD	94067008	125 A5	4.33R		6.7	18.1	TL	
180/70 R 8 IMP (18X7 R 8)	STANDARD	94067602	120 A8	4.33R		6.7	18.1	TL	E11-106R-006845
6.00 R 9	STANDARD	94063901	121 A5	4.00E		6.3	21.3	TL	
6.50 R 10	STANDARD	94066247	128 A5	5.00F	5.50 F	6.9	23.3	TL	
7.00 R 12	STANDARD	94066209	136 A5	5.00S		7.7	26.6	TL	
7.00 R 15	STANDARD	94066834	143 A5	5.50	5.00	7.8	29.1	TL	
8.25 R 15	STANDARD	94063635	153 A5	6.5	7.0	9.4	33.2	TL	

Printed on 4/27/2024 6:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..