

LIFTMAX LM 81 - Teknik Özellikler



Description

LIFTMAX LM 81, ağır forklift ve terminal traktörler için özel olarak tasarlanmış ve üretilmiştir. Benzersiz Antistatik sırt hamuru ile birlikte sert ve sağlam sırt deseni, aşınmaya karşı mükemmel özellikler ve uzun bir kullanma süresi sunar. Güçlü Tamçelik gövde ve güçlendirilmiş yanak, üstün çekiş ile birlikte kaldırma modu sırasında maksimum sabitleme ve kullanım sağlar. Ayrıca, radyal gövdesi, daha iyi bir sürüş konforu sağlamak ve operatörün güvenini artırmak için yüzeylerin düzensizliklerini emer. LIFTMAX LM 81, Antistatik uyumludur ve tüm boyutları araçtan statik yükü dağıtma kapasitesine sahiptir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Saman biçerdöveri
Endüstriyel: Forklift

Version	STANDARD
Type	TL
Tyre Size	150/75 R 8
LI/SS	113 A5

Dimensions US Standard

Usa code	94069316
Overall Width (inch)	5.9
Overall Diameter (inch)	16.9
Rim Rec	4.33R

Load capacity (lbs)

mph / psi	145
15	2535

Printed on 4/24/2024 8:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..