

LOADER PLUS - Teknik Özellikler



Description

LOADER PLUS (L-3) yükleyiciler için özel olarak tasarlanmış, çapraz kuşaklı bir lastiktir. Diş deseni bileşimi kesilme ve parçalanmaya karşı dayanıklı özellikler taşıyor ve yükleme ve kazma çalışmaları için özellikle uygundur.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Dozer • Yükleyici
Yoldışı: Dozer • Yükleyici

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	760
Overall Diameter (mm)	1860
Static Loaded Radius (mm)	849
Rolling Circumference (mm)	5544
Rim Rec	25.00/3.5
TRA Code	L3

Load capacity (Kg)

km/h / bar	5.00
10	19250

Printed on 2/27/2024 10:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..