

LOADER SPECIAL - Teknik Özellikler



Description

LOADER SPECIAL (L-5) yükleyicilerinizi hareket halinde tutan ve ağır yük gerektiren taş taşıma çalışmalarında üstün verimlilik sağlayan, çapraz kuşaklı bir lastiktir. En uygun çekiş ve kesilmeye karşı olağanüstü dayanıklılık, verimliliği artırır.

UM

International Standard

Construction

BIAS

Machinery

Yoldışı: Dozer • Yükleyici

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	770
Overall Diameter (mm)	1930
Static Loaded Radius (mm)	884
Rolling Circumference (mm)	5753
Rim Rec	25.00/3.5
TRA Code	L5

Load capacity (Kg)

km/h / bar	4.25
10	17500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/11/2024 10:25 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..