

LP 450 - Teknik Özellikler



Description

LP 450 taşımacılık uygulamalarındaki alçak platformlar için yola yönelik bir lastiktir. Bu yüksek hızlı lastik, uzun bir lastik ömrünün yanı sıra yakıttan önemli ölçüde tasarruf sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Düşük platformlu treyler

Version	STANDARD
Type	TL
Tyre Size	9 - 14.5

Dimensions International Standard

Ply Rating	14
Section Width (mm)	246
Overall Diameter (mm)	712
Static Loaded Radius (mm)	322
Rolling Circumference (mm)	2115
Rim Rec	7.00 MH

Load capacity (Kg)

	km/h / bar	7.90
	100 LS	1625
	100 LD	1430

Printed on 4/25/2024 7:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..