



## LT TR 182 - Veri Sayfasını İndir



### Description

LT TR 182 hafif kamyonlarla taşımacılık çalışmaları için uygundur. Yüksek hızlı lastik, yola yöneliktir ve yakıt tüketimini önemli ölçüde azaltır. LT TR 182 lastiğın takılması da oldukça kolaydır.

### UM

International Standard

### Construction

 BIAS

### Machinery

Endüstriyel: Kamyonet

| SIZE     | Version  | PR | RIM REC | RIM ALT | SW  | OD  | Type |
|----------|----------|----|---------|---------|-----|-----|------|
| 8 - 14.5 | STANDARD | 12 | 6.00 MH |         | 207 | 710 | TL   |
| 8 - 14.5 | STANDARD | 14 | 6.00 MH |         | 207 | 710 | TL   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/4/2024 12:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..