

MAGLIFT ECO - Teknik Özellikler



Description

MAGLIFT ECO özellikle forkliftler için tasarlanmıştır. Lastik, maksimum sabitleme ve optimize edilmiş yük dağılımı sağlayan geniş bir diş desenine sahiptir. Güçlendirilmiş yapısı kayma risklerini ortadan kaldırırken, özel olarak tasarlanmış jant koruyucusu tekerlek hasarına karşı koruma sağlar. MAGLIFT ECO, daha iyi verimlilik için mükemmel çekişin yanı sıra düşük yuvarlanma direnci ve düşük ısı birikimi sergiler.

UM

International Standard

Construction

◆ SOLID

Machinery

Endüstriyel: Forklift

Version

STANDARD

Type

Tyre Size

6.00 - 9

Dimensions International Standard

TKPH	1
Section Width (mm)	130
Overall Diameter (mm)	522
Rim Rec	4.00 E - 9

Load capacity (Kg)

km/h / bar	-
25 LOAD WHEEL	1885
25 STEER WHEEL	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/4/2024 4:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..