

MAGLIFT EXCAVATOR - Veri Sayfasını İndir



Description

MAGLIFT EKSKAVATÖR kazma, yükleme ve yol yapım işlemlerinde çalışan tekerlekli ekskavatörler için özel olarak tasarlanmıştır. Lastik, mükemmel kesik ve kopma direnci ve daha uzun lastik kullanım ömrü sağlayan özel bir sırt hamurundan üretilmiştir. Agresif sırt tasarımı, ağır hizmet koşullarında bile mükemmel yanıl çekişle birlikte yüksek düzeyde kullanım konforu ve ayrıca üstün kendi kendini temizleme özellikleri sunar. Güçlendirilmiş damak yapısı en iyi kavramayı sağlar ve operasyonlar sırasında kayma riskini ortadan kaldırır, özel damak şekli ise jant üzerindeki montaj işlemlerini basitleştirir. MAGLIFT EKSKAVATÖR, operatörlerin güvenebileceği delinmeyen ve bakım gerektirmeyen bir lastiktir.

UM

US Standard

Construction

◆ SOLID

Machinery

Endüstriyel: Ekskavatör

SIZE	Version	USACode	RIM REC	RIM ALT	OW	OD	Type
10.00 - 20	STANDARD	94071197	7.50 - 20		9.4	39.8	
10.00 - 20	STANDARD	94071203	8.00 - 20		9.7	39.8	
10.00 - 20	STANDARD	94071180	7.00 - 20		9.4	39.8	
12.00 - 20	STANDARD	94071111	8.50 - 20		10.4	43.3	
12.00 - 20	STANDARD	94071173	8.00 - 20		10	43.3	

Printed on 5/3/2024 9:42 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..