

## MAGLIFT PREMIUM - Teknik Özellikler



### Description

MAGLIFT PREMIUM özellikle limanda yapılan ağır forklift çalışmaları, madencilik veya hurdalık uygulamaları için tasarlanmış sağlam bir lastiktir. Sert ve sağlam desenli ekstra derin sırt (standart versiyona kıyasla %25 daha fazla), mükemmel direksiyon kontrolüne ek olarak olağanüstü ön ve yanar çekiş sağlar. Benzersiz sırt hamuru yüksek düzeyde kesik ve kopma direnci sağlayarak lastiğin kullanım ömrünü uzatır. Düşük yuvarlanma direnci ve kusursuz çalışma ek özelliklerdir.

### UM

US Standard

### Construction

◆ SOLID

### Machinery

Endüstriyel: Forklift

Version

STANDARD

Type

Tyre Size

7.00 - 12

## Dimensions US Standard

Usa code	94055616
Section Width (inch)	6.4
Overall Diameter (inch)	26.1
Rim Rec	5.00 S - 12

## Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	6435
15 STEER WHEEL	4940

Printed on 5/9/2024 12:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..