

MAGLIFT RIM GUARD - Teknik Özellikler



Description

MAGLIFT (JANT KORUYUCUSU), endüstriyel ve lojistik tesislerde kullanılan ağır hizmet tipi forkliftler için özel olarak geliştirilmiş ve tasarlanmıştır. Sert ve sağlam sırt deseni, üstün ileri ve yanal çekişin yanı sıra mükemmel direksiyon kontrolü sağlar. Ek olarak geniş merkezi kuşak, düşük yuvarlanma direnci sağlar. MAGLIFT (JANT KORUYUCUSU) ürününün sert yapısı, yüksek yük kapasitesine ve olağanüstü bir konfora sahip olmakla birlikte, özel olarak tasarlanmış jant koruması tekerlek hasarına karşı korumayı garanti eder. Ek olarak, bu lastik mükemmel bir kesilme ve kopma direnci gösterir ve daha uzun lastik ömrü sağlar. MAGLIFT (JANT KORUYUCUSU) ürününün takviyeli yapısı kayma riskini ortadan kaldırırken, özel damak şekli jantta montaj işlemlerini basitleştirir.

UM

US Standard

Construction

◆ SOLID

Machinery

Endüstriyel: Forklift

Version

STANDARD

Type

Tyre Size

6.50 - 10

Dimensions US Standard

| | |
|-------------------------|-------------|
| Usa code | 94066285 |
| Section Width (inch) | 6.1 |
| Overall Diameter (inch) | 22.6 |
| Rim Rec | 5.00 F - 10 |

Load capacity (lbs)

| mph / psi | - |
|----------------|------|
| 15 LOAD WHEEL | 5160 |
| 15 STEER WHEEL | 3970 |

Printed on 4/27/2024 10:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..