

MH TR 182 - Teknik Özellikler



Description

MH TR 182 taşınabilir ev araçlarıyla taşımacılık çalışmaları için uygundur. Yola yönelik, yüksek hızlı, yakıt tüketimini önemli ölçüde azaltan bir lastiktir. MH TR 182 ömür döngüsü boyunca, uzun süreli dayanıklılık ve yüksek performans sağlar.

UM

International Standard

Construction



Machinery

Zirai: Seyyar ev

Version	STANDARD
Туре	TL
Tyre Size	8 - 14.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	207
Overall Diameter (mm)	710
Rim Rec	6.00 MH

Load capacity (Kg)

km/h / bar	5.90
100	1180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 9:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..