

MINE STAR - Teknik Özellikler



Description

MINE STAR ağır yük gerektiren yeraltı madenciliği çalışmaları için kusursuz bir tercih olan, çapraz kuşaklı bir lastiktir. Kesilme/parçalanmalara karşı yüksek dayanıklılık sunarak gelişmiş işletme verimliliği sağlar. MINE STAR özel bir bileşikten üretilmiştir ve lastik ömrünü uzatan özel bir diş desenine sahiptir.

UM

International Standard

Construction

❖ BIAS

Machinery

Yoldışı: Yeraltı madenciliği aracı

Version	STANDARD
Type	TT
Tyre Size	35 X 15 - 15

Dimensions International Standard

Ply Rating	32
Section Width (mm)	372
Overall Diameter (mm)	885
Rim Rec	11.0
Rim Alt	11.50 ; 11.00 BD
Tread Depth	24

Load capacity (Kg)

km/h / bar	10.00
10	5580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 12:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..