

## MINE STAR - Teknik Özellikler



### Description

MINE STAR ağır yük gerektiren yeraltı madenciliği çalışmaları için kusursuz bir tercih olan, çapraz kuşaklı bir lastiktir. Kesilme/parçalanmalara karşı yüksek dayanıklılık sunarak gelişmiş işletme verimliliği sağlar. MINE STAR özel bir bileşikten üretilmiştir ve lastik ömrünü uzatan özel bir diş desenine sahiptir.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Yoldışı: Yeraltı madenciliği aracı

Version	STANDARD
Type	TL
Tyre Size	55 X 19.00 - 25

## Dimensions International Standard

Ply Rating	50
Section Width (mm)	480
Overall Diameter (mm)	1400
Static Loaded Radius (mm)	632
Rolling Circumference (mm)	4280
Rim Rec	14.00
TRA Code	L5

## Load capacity (Kg)

km/h / bar	10.00
5	17305
10	15315
15	14245
25	13020

Printed on 12/11/2023 6:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..