

## MINEFORCE - Teknik Özellikler



### Description

MINEFORCE, madencilik ve taş ocağı operasyonlarında nakliye kamyonları için özel olarak tasarlanmış çapraz katlı bir lastiktir. MINEFORCE yüksek performanslı taşıma kamyonu lastiği, BKT'nin kayalık, aşındırıcı ve zorlu madencilik ortamlarına yönelik ürettiği yenilikçi ürünüdür. Bu üründe, sert, kayalık ve zorlu madencilik koşulları için özel olarak geliştirilmiş benzersiz bir sırt tasarımı mevcuttur. Sert dişli geniş temas bandı, sırt aşınması ve daha uzun bir kullanım süresi sağlar.

### UM

US Standard

### Construction

BIAS

### Machinery

Yoldışı: Sabit kaya kamyonu

Version	STANDARD
Type	TL
Tyre Size	27.00 - 49

## Dimensions US Standard

Usa code	94070107
Ply Rating	48
TMPH	325
Overall Width (inch)	29.1
Overall Diameter (inch)	106.1
Static Loaded Radius (inch)	49.3
Rolling Circumference (inch)	314.4
Rim Rec	19.50/4.0
TRA Code	E4

## Load capacity (lbs)

mph / psi	83	112
30	55100	-
5	-	96500

Printed on 9/30/2023 5:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..