

## MP 567 - Teknik Özellikler



### Description

MP 567, arazi ve kara yolu taşımacılığı ve belediye/bakım işlemleri için uygun bir tarımsal sanayi lastiğidir. Teleskopik yükleyiciler ve uygulamalı makineler için mükemmel lastiktir. MP 567 lastik, tüm hava koşullarında iyi çekiş ve mükemmel kendi kendini temizleme özellikleri sunar. Bu lastik, daha uzun kullanım ömrü ile birlikte konforlu bir sürüş deneyimi sağlar.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: Uygulamalı makine • Teleskopik yükleyici  
Endüstriyel: Teleskopik yükleyici • Genel kullanım aracı / Kompaktör

Version	IMPLEMENT
Type	TL
Tyre Size	10.0/75 - 15.3
LI/SS DRIVE WHEEL	111 A8
LI/SS FREE ROLLING	123 A8

## Dimensions US Standard

Usa code	94057542
Ply Rating	10
TMPH	1
Section Width (inch)	10.2
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14.4
Rolling Circumference (inch)	94.5
Rim Rec	9.0
ECE	E11-106R-003526

## Load capacity (lbs)

mph / psi	56
25 FR	3415
25 DW	2405

Printed on 4/25/2024 8:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..