

MP 567 - Teknik Özellikler



Description

MP 567, arazi ve kara yolu taşımacılığı ve belediye/bakım işlemleri için uygun bir tarımsal sanayi lastiğidir. Teleskopik yükleyiciler ve uygulamalı makineler için mükemmel lastiktir. MP 567 lastik, tüm hava koşullarında iyi çekiş ve mükemmel kendi kendini temizleme özellikleri sunar. Bu lastik, daha uzun kullanım ömrü ile birlikte konforlu bir sürüş deneyimi sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine • Teleskopik yükleyici
Endüstriyel: Teleskopik yükleyici • Genel kullanım aracı / Kompaktör

Version	STANDARD
Type	TL
Tyre Size	14.5 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	360
Overall Diameter (mm)	1116
Static Loaded Radius (mm)	495
Rolling Circumference (mm)	3315
Rim Rec	11
Rim Alt	12 SDC

Load capacity (Kg)

km/h / bar	4.00
90	2575
40	2960

Printed on 4/28/2024 10:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..