

## MP 567 - Teknik Özellikler



### Description

MP 567, arazi ve kara yolu taşımacılığı ve belediye/bakım işlemleri için uygun bir tarımsal sanayi lastiğidir. Teleskopik yükleyiciler ve uygulamalı makineler için mükemmel lastiktir. MP 567 lastik, tüm hava koşullarında iyi çekiş ve mükemmel kendi kendini temizleme özellikleri sunar. Bu lastik, daha uzun kullanım ömrü ile birlikte konforlu bir sürüş deneyimi sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Uygulamalı makine • Teleskopik yükleyici  
Endüstriyel: Teleskopik yükleyici • Genel kullanım aracı / Kompaktör

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20 (405/70 - 20)

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	405
Overall Diameter (mm)	1128
Static Loaded Radius (mm)	490
Rolling Circumference (mm)	3350
Rim Rec	13 SDC
Rim Alt	12
ECE	E4-54R-0022639

## Load capacity (Kg)

km/h / bar	3.50
90	2900
40	3340

Printed on 4/25/2024 11:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..