

MP 585 - Teknik Özellikler



Description

MP 585, belediye/bakım uygulamalarında kullanılan çok amaçlı araçlar için uygun olan bir tarımsal sanayi lastiğidir. Bu lastik, en zorlu çalışma koşullarında ve aynı zamanda yüksek hızlarda maksimum sabitleme ve dayanıklılık sunan bir blok diş deseni ile özel olarak tasarlanmıştır.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Genel kullanım aracı

Endüstriyel: Genel kullanım aracı / Kompaktor

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

Dimensions US Standard

Usa code	94038404
Ply Rating	12
Section Width (inch)	13.2
Overall Diameter (inch)	41.3
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	123.2
Rim Rec	11
Rim Alt	12 SDC
ECE	E4-54R-0022635

Load capacity (lbs)

	mph / psi	51
	55	4410
	30	4940

Printed on 4/17/2024 5:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..