

MP 590 - Teknik Özellikler



Description

MP 590, teleskopik yükleyiciler ve forkliftlerle yükleme işlemleri için uygun bir tarımsal sanayi lastiğidir. Bu lastik, iyi bir çekiş ve mükemmel sabitleme ile daha yüksek dayanıklılık sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Teleskopik yükleyici
Endüstriyel: Forklift • Teleskopik yükleyici • Genel kullanım aracı / Kompaktör

Version STANDARD

Type TL

Tyre Size 18 - 22.5
(445/65 - 22.5)

Dimensions International Standard

Ply Rating	16
Section Width (mm)	480
Overall Diameter (mm)	1190
Static Loaded Radius (mm)	530
Rolling Circumference (mm)	3534
Rim Rec	14.0
ECE	E11-106R-003019

Load capacity (Kg)

km/h / bar	5.50
40 DW	4875
30 DW	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/12/2024 11:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..