

MP 600 - Teknik Özellikler



Description

MP 600, teleskopik yükleyiciler ve uygulamalı makineler kullanılan belediye/bakım operasyonları için uygun, konforlu bir sürüş deneyimi sağlayan bir tarımsal sanayi lastiğidir. Bu lastik, uzun bir kullanım ömrü ile birlikte iyi çekiş ve mükemmel kendi kendini temizleme özellikleri sunar.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine • Teleskopik yükleyici
Endüstriyel: Teleskopik yükleyici • Genel kullanım aracı / Kompaktör

| | |
|-------------------|-------------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 400/70 - 24 (16.0/70 - 24) |
| LI/SS DRIVE WHEEL | 158 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94049318 |
| Ply Rating | 18 |
| Section Width (inch) | 15.9 |
| Overall Diameter (inch) | 46.7 |
| Static Loaded Radius (inch) | 21.5 |
| Rolling Circumference (inch) | 139 |
| Rim Rec | 13 SDC |
| Rim Alt | 12 |
| ECE | E11-106R-003641 |

Load capacity (lbs)

| mph / psi | 65 |
|-----------|------|
| 25 DW | 9370 |
| 30 DW | 9090 |

Printed on 4/27/2024 8:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..